



Wymiary (m)	Modele AmphiMaster							
	AM 60	AM 80	AM 140	AM 200	AM 220	AM 300	AM 350	AM 400
	Waga koparki 5-6 ton	Waga koparki 6-8 ton	Waga koparki 12-14 ton	Waga koparki 20-22 ton	Waga koparki 24-27 ton	Waga koparki 28-30 ton	Waga koparki 33-36 ton	Waga koparki 40-45 ton
A	5,56	6,28	9,30	9,65	9,65	10,90	11,90	11,77
B	2,75	3,17	4,00	4,15	4,15	5,40	6,00	6,50
C	0,85	1,50	2,18	2,75	3,00	3,12	3,40	3,65
D	7,90	8,87	12,30	13,55	14,40	15,00	16,60	17,00
E	2,40	2,78	2,95	3,47	3,60	4,10	4,15	4,20
F	1,52	1,62	1,90	2,17	2,20	2,30	2,35	2,40
G (min/max)	2,75 / 3,45	3,38 / 4,18	4,22 / 5,32	4,80 / 6,28	5,47 / 6,91	6,21 / 7,21	6,27 / 7,27	5,97 / 6,97
H (min/max)	2,75 / 3,45	3,38 / 4,18	3,95 / 5,05	4,47 / 5,95	5,17 / 6,61	5,91 / 6,91	5,97 / 6,97	5,97 / 6,97
I (min/max)	1,75 / 2,45	2,06 / 2,86	2,50 / 3,60	2,85 / 4,33	3,25 / 4,69	3,99 / 4,99	4,02 / 5,02	4,02 / 5,02
J	1,00	1,30	1,45	1,62	1,92	1,92	1,92	1,95
K	1,01	1,05	1,14	1,30	1,30	1,30	1,13	1,16
L	1,46	1,50	1,70	2,03	2,03	2,03	2,03	2,19
M	3,46	3,46	3,90	4,10	4,20	4,23	4,25	4,37
N	1,50	2,17	2,50	2,75	2,85	2,95	3,00	3,09
R	7,28	9,50	11,90	14,00	14,60	15,10	15,60	15,90
S	6,15	8,50	10,00	12,10	12,20	13,00	13,30	13,20
T	7,00	9,00	12,00	14,00	15,00	16,00	17,00	18,00
U1	4,00	6,20	8,00	8,80	9,80	10,60	11,50	12,20
U2	3,30	5,50	6,60	6,90	7,75	8,20	9,40	10,00
Pojekność łyżki (m3)	0,13	0,25	0,40	0,50	0,70	0,80	0,90	1,10