



Wymiary (m)	Modele AmphiMaster									
	AM 60	AM 70	AM 80	AM 140	AM 200	AM 220	AM 300	AM 350	AM 400	AM 450
	Waga koparki 3,5 - 4,5 t	Waga koparki 5 - 6 t	Waga koparki 7 - 8 t	Waga koparki 12 - 14 t	Waga koparki 20 - 23 t	Waga koparki 24 - 27 t	Waga koparki 28 - 30 t	Waga koparki 33 - 38 t	Waga koparki 39 - 43 t	Waga koparki 44 - 48 t
A	5.56	6.42	6.95	9.29	9.63	9.63	10.84	11.84	11.75	11.76
B	2,75	2.90	3.20	4.30	4.50	4.50	5.20	5.70	6.00	06.00
C	0,85	1.58	1.75	2.13	2.85	3.00	3.19	3.50	3.50	3.56
D	7,90	7.47	9.25	12.24	13.55	14,41	15,55	16,59	17,20	18.00
E	2,40	2.28	2.90	2,95	3,47	3.55	4,10	4,12	4,28	4.30
F	1,52	1.62	1.73	1.84	2.17	2,20	2.35	2,35	2,40	2.40
G (min/max)	2.78 / 3.48	2.80/3.60	3.39 / 4.19	4.02 / 5.12	4.50 / 5.98	5.20 / 6.64	5.94 / 6.94	6.00 / 7.00	6.00 / 7.00	6.43/7.43
H (min/max)	2.75 / 3.45	52.76/3.56	3.36 / 4.16	3.94 / 5.04	4.47 / 5.95	5.17 / 6.61	5.91 / 6.91	5,97 / 6,97	5,97 / 6,97	6.40/7.40
I (min/max)	1,75 / 2,45	1.76/2.56	2,06 / 2,86	2.49 / 3.59	2,85 / 4,33	3,25 / 4,69	3,99 / 4,99	4,02 / 5,02	4,02 / 5,02	4.25/5.25
J	1,00	1.00	1,30	1,45	1,62	1,92	1,92	1,95	1,95	2.15
K	1,01	1.01	1,15	1,12	1,30	1,30	1,29	1,13	1,16	1.10
L	1,46	1.51	1,65	1,69	2,03	2,03	2,03	2,03	2,19	2.19
M	3,46	3.55	3,65	3,77	4,08	4,12	4,27	4,30	4,30	4.36
N	1,50	1.95	2,26	2,45	2,54	2,85	2,96	2,99	3,09	3.53
R	6,50	7.10	7,95	11,40	12,40	13,70	14,60	15,30	15,20	16.30
S	5,20	5.75	6,30	9,30	10,50	11,40	12,10	12,80	12,70	13.80
T	7,00	6.55	8,00	12,00	14,00	15,00	16,00	17,00	18,00	20.00
U1	3,70	3.50	3,80	7,30	8,90	9,40	9,90	11,00	12,50	13.90
U2	3,50	3.50	3,40	6,50	7,20	7,20	8,50	9,60	10,40	11.30
Pojekność łyżki (m³)	0,13	0.11	0,25	0,40	0,50	0,70	0,80	0,90	1,10	1.10